



**NOTES**

1. ALL SURVEY MARKERS SHALL BE CENTER PUNCHED AFTER PLACEMENT.
2. 1-1/2" MINIMUM DIAMETER ALUM. OR BRASS CAP W/PLS# PERMANENTLY ATTACHED PRIOR TO PLACEMENT.
3. MONUMENT POT SHALL BE SET 3/8"-5/8" BELOW FINISHED ROADWAY SURFACE.
4. CONC COLLAR SHALL BE LEFT 2" BELOW FINISHED ASPH SURFACE. TOP OF CONC SHALL RECEIVE A ROUGH BROOM FINISH. PLACE 2" OF TYPE 3 ASPH AROUND MONUMENT POT. APPLY SS-1 TACK COAT TO TOP OF CONC BEFORE PLACING ASPH PAVING, & SEAL ASPH SURFACE W/SS-1 TACK COAT & SAND. CHIP SEAL, SAND SEAL, SLURRY SEAL OR FOG SEAL PAVED SURFACE AS REQ'D BY PLANS OR SPECS.
5. CONC SHALL BE FLUSH W/TOP OF SURVEY POT WHEN NOT LOCATED IN ASPH PAVING.

NO.	REVISION	DATE	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION	SECTION
1	REDRAW	10/09sw	MONUMENTS	1
2				DRAWING NO.
3				1-27
4				DATE 3/10 sw PAGE 38