


Class "C" backfill (Typ)  
See note 8 on dwg. 2-10



Detail "A"

See detail "A"

1" Diameter holes (8 Total)

1.  $\frac{3}{8}$ " diameter smooth steel rod with 90° 2" bend
2.  $\frac{5}{16}$ " diameter X 4" Lag Eye Bolt epoxied into catch basin wall opposite of the pipe outlet
3. 2- $\frac{3}{4}$ " X  $\frac{5}{16}$ " Aluminum Snap Ring attached to  $\frac{3}{8}$ " rod.
- 4a.  $\frac{1}{4}$ " Nylon Rope attached to top Log Eye Bolt and Snap Ring.
- 4b Attach Oil Sock to Snap Ring.
5. Oil Sock (Sorbert Model #L90898 or approved equivalent)
6. Nylon ties


**NOTES**

1. Carson City – Not permitted in Public Ways.
2. Not permitted for use in Lyon County.
3. Fallon – See Agency Section
4. "Bee Hive" grate (Neenah #R-2563; R-2564 or equivalent) may be used in unimproved or landscape areas as approved by the engineer.
5. Reno – For use only in unimproved areas. A concrete collar shall be constructed as shown.
6. Outlet pipe to me minimum size as shown on Drawing 2-8.
7. Washoe County – Concrete collar shall be 18" in width at all locations.
7. In areas of fine grained or expansive soils, class "C" backfill depth shall be 24" below bottom of barrel.

$\frac{5}{16}$ " Aluminum Snap Ring detail



$\frac{5}{16}$ " Stainless Lag Eye Bolt Detail



NO.			REVISD	DATE	STANDARD DETAILS FOR PUBLIC WORKS CONSTRUCTION	SECTION:
1					<h2 style="margin: 0;">CATCH BASIN TYPE 3</h2>	2
2				DRAWING NO:		2-10.1
3				DATE:		8-07
				PAGE:		13.1